

PCTel PCI Half Height Internal Modem



Features

Data

Supported Communication Standards

- *K56flex
- *ITU-T V.90, V.34, V.34bis, V.32, V.22bis, V.23, V.21, Bell 212A, Bell 103

Data Compression

- *V.42 & MNP 5

Error Correction

- *V.42 & MNP 2-4

Fax

Supported Communication Standards

- *ITU-T V.17, V.29, V.27ter, V.21 Channel 2
- *EIA Class 1

Operating System Compatibility

- *Windows 98, ME
- *Windows NT, 2000
- *DOS
- *Linux

General Features

- *Caller ID
- *TAM support
- *Voice/Fax/Data auto detection
- *Microsoft Windows TAPI compliant
- *Full-duplex Speakerphone
- *ITU-T V.80 for H.324 interface support
- *Compliant with PCI specification Rev. 2.2
- *High-Throughput Virtual UART, DTE rate up to 115.2

Required CPU

- *Pentium MMX 166 MHz or AMD K6 MMX 200 MHz or better

Operating Environment

- *Temperature: 0 – 40 degrees Celsius
- *Humidity: 10% - 90%

Approval

- *FCC Part 15 & 68, CE
- *CTR 21

3JTech. Co., Ltd.

Tel: 886-2-2500-6916

URL: www.3jtech.com.tw